

Galvax 50103

SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 1 of 6

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label : Galvax Cold Galvanizing Paint

Product Code(s) : 50103

Recommended use of the chemical and restrictions on use : Industrial Coating Use pattern Professional Use Only

Recommended restrictions : None Known.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.

85 Paris Street

Everett, Massachusetts, 02149 U.S.A.

Email: sales@dampney.com

Supplier's Telephone: (617) 389-2805 24 Hr. Emergency Tel: Chemtrec 1-800-424-9300 (North America)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical Gray liquid. Solvent odor.

Classification:

Flammable Liquid - Category 3 Specific Target Organ Toxicity - Single Exposure - Category 3 (Central Nervous System) Aspiration Hazard - Category 1 Carcinogen - Category 2

Label elements

Hazard pictogram(s)







Signal Word Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

PREVENTION:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, lighting, mixing, application equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust, fume, gas, mist, vapours, or spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, eye protection, and face protection.

P281 Use personal protective gloves, protective clothing, eye protection, and face protection.



Dampney Company, Inc. 85 Paris Street Everett, Massachusetts, U.S.A.02149 Email: sales@dampnev.com Telephone: (617) 389 2805

Galvax 50103

SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 2 of 6

SAFETY DATA SHEET

RESPONSE:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or hospital emergency room.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry chemical, CO2, water spray (fog) or foam to extinguish.

P403 + P233 + P235 (S) Store in a cool, well-ventilated place. Keep container tightly closed.

P405 Store locked up.

DISPOSAL:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS-No | Weight %* |
|----------------------|------------|-----------|
| Zinc Dust | 7440-66-6 | 71.40 |
| Mineral Spirits | 64742-47-8 | 8.39 |
| Aromatic Hydrocarbon | 64742-95-6 | 6.53 |

SECTION 4. FIRST-AID MEASURES

First aid measures for different exposure routes

General advice Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.

Flush thoroughly with water. If irritation occurs, get medical assistance. Eye contact

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before

Inhalation Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate

respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical

assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Seek immediate medical attention. Do not induce vomiting. Ingestion

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water.

Specific hazards during firefighting: Do not allow run-off from fire fighting to enter drains or water courses.

Specific extinguishing methods: Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking

water supply. Use a water spray to cool fully closed containers.

Protective Equipment and Precautions for Firefighters:

Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect

personnel.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions Environmental precautions Methods for Containment

Eliminate all ignition sources. Maintain adequate ventilation to keep the exposure levels below the DELS. Report spills as required by local and federal regulations. Avoid contaminating ground and surface water

Prevent further leakage or spillage if safe to do so. Dike spill area to contain liquid.

Methods for cleaning up Contain liquid and collect with a non-combustible material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling: Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or ground procedures. However, bonding and



Telephone: (617) 389 2805

Galvax 50103

SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 3 of 6

SAFETY DATA SHEET

grounds may not eliminate the hazard from static accumulation.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage Keep containers tightly closed in a cool, well-ventilated place. conditions

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters:

| Chemical Name | Standard | Limit | |
|----------------------|------------------|--------------------|--|
| Zinc Dust | None established | None established | |
| Mineral Spirits | RCP – TWA | 197 ppm 1200 mg/m3 | |
| Aromatic Hydrocarbon | RCP – TWA | 19 ppm 100 mg/m3 | |

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

TWA: Time Weighted Average PEL: Permissible Exposure Limit

Exposure controls

Engineering Measures: Ventilation systems. Use adequate ventilation to keep the exposure levels below the recommended exposure limits.

Individual protection measures, such as personal protective equipment.

General information Eye bath. Safety shower. Washing facilities.

Eye/Face Protection: Safety glasses with side-shields.

Skin and body protection: Chemical resistant apron. Protective gloves.

Respiratory protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with

regulatory requirements, if applicable.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Gray Liquid Odour : Solvent

pH : No information available

Melting/Freezing point

Boiling point

Flash point

Evaporation rate (BuAe = 1)

Lower flammable limit (% by vol.)

Upper flammable limit (% by vol.)

Mot available

300°F (149°C)

105°F (40°C)

10035

1.0

12.6

Vapour density (air =1) : Heavier than air

Specific gravity : 2.71418 at 60°F (15.6°C)

Weight per gallon : 23 lbs

Partition coefficient : Not determined VOC : 3.77 lbs/Gal

SECTION 10. STABILITY AND REACTIVITY

Reactivity Stable under recommended storage conditions

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions" None under normal processing.

Conditions to Avoid: Keep away from heat, sparks, flame and other potential ignition sources.

Incompatible Materials: Store away from strong oxidizers.

Hazardous Decomposition Products: Carbon monoxide and unidentified organics may be formed.



Telephone: (617) 389 2805

Galvax 50103 SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 4 of 6

SAFETY DATA SHEET

Information on likely routes of exposure

Skin contact Yes Eye contact Yes

Inhalation Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

Ingestion Harmful if swallowed.

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation | | |
|----------------------|------------------|--------------------|------------------|--|--|
| Zinc Dust | None established | None established | None established | | |
| Mineral Spirits | Rat >5000 mg/kg | Rabbit >5000 mg/kg | Rat 4951 mg/m3 | | |
| Aromatic Hydrocarbon | Rat 3492 mg/kg | Rabbit >3160 mg/kg | Rat 6193 mg/m3 | | |

EFFECTS OF OVEREXPOSURE:

High vapor concentrations (> approx. 1000 ppm) are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anesthetic, and have other central nervous system effects.

PRIMARY ROUTE(S) OF ENTRY:

(X) Dermal (X) Inhalation () Ingestion

EMERGENCY AND FIRST AID PROCEDURES:

Eyes - flush thoroughly with running water for 15 minutes, including under eyelids. Get medical attention.

Skin - promptly remove contaminated clothing and wash affected areas thoroughly with soap and water. If irritation occurs get medical attention. Wash contaminated clothing thoroughly before re-use.

Inhalation - if overcome by vapor, remove to an area free from risk of further exposure and call a physician immediately. Administer oxygen or artificial respiration as needed.

Ingestion - do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

MEDICAL CONDITIONS PRÔNE TO AGGRAVATION BY EXPOSURE:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

SECTION 12. ECOLOGICAL INFORMATION

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to microorganisms | Toxicity to daphnia and other aquatic invertebrates |
|--|---|--|----------------------------|---|
| Zinc Powder 7440-66-6 | 0.11 -0.271 mg/LEC50 Pseudokirchneriella subcapitata 96h static | 0.59 mg/L LC50 Oncorhynchus mykiss 96h semi-static | - | 0.139-0.908 mg/LEC50 Daphnia magna 48h Static |
| Mineral Spirits 64742-47-8 | >1000 mg/l EL50 Pseudokirchneriella subcapitata 72h | >1000 mg/l LL50 Oncorhynchus mykiss 96h | - | 1000 mg/l ELO Daphnia magna 48h |
| Aromatic Hydrocarbon 64742- 95-6 | 2.9 mg/l Erl50 Pseudokirchneriella subcapitata 72h | 9.2 mg/l LL50 Oncorhynchus mykiss 96h | - | 3.2 mg/l EL50 Daphnia magna 48h |

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice.

Methods of Disposal : Dispose in accordance with all applicable regulations.

SECTION 14. TRANSPORTATION INFORMATION

| Regulatory Information | UN Number | UN proper shipping name | Transport hazard class(es) | Packing Group | Label |
|---|-----------|-------------------------|----------------------------|---------------|-----------|
| 49CFR/DOT | UN1263 | Paint related material | 3 | III | FLAMMABLE |
| Additional information When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149} special provision 149. | | | | | |



Telephone: (617) 389 2805

Galvax 50103

SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 5 of 6

SAFETY DATA SHEET

| TDG | UN1263 | Paint related material | 3 | III | FLAMMABLE |
|------------------------|---|------------------------|---|-----|-----------|
| Additional information | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. | | | | |
| IMDG | UN1263 | Paint related material | 3 | III | FLAMMABLE |
| Additional information | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. | | | | |
| ICAO/IATA | UN1263 | Paint related material | 3 | III | FLAMMABLE |
| Additional information | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. | | | | |

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). None.

SARA 311/312 Hazard Categories Immediate Health Hazard Yes Delayed Health Hazard Yes Fire Hazard Yes

TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory.

Mineral Spirits on the following state RTK lists.

Pennsylvania New Jersey

SECTION 16. OTHER INFORMATION

NFPA

Health hazard 1 Flammability 2 Reactivity 1

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980

CFR: Code of Federal Regulations CSA: Canadian Standards Association DOT: Department of Transportation EC50: Effective Concentration 50%.

EINECS: European Inventory of Existing Commercial chemical Substances

ENCS: Existing and New Chemical Substances EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank IARC: International Agency for Research on Cancer

IECSC: Inventory of Existing Chemical Substances

IMDG: International Maritime Dangerous Goods Inh: Inhalation

KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List

LC: Lethal Concentration



Telephone: (617) 389 2805

Galvax 50103

SDS Preparation Date (mm/dd/yyyy): 08/18/2021

Page 6 of 6

SAFETY DATA SHEET

LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NJ: New Jersey

NIOSH: National Institute of Occupational Safety and Health

NOEC: No observable effect concentration

NTP: National Toxicology Program

OECD: Organisation for Economic Co-operation and Development

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

RCRA: Resource Conservation and Recovery Act

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References:

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM). OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015 European Chemicals Agency, Classification Legislation

Prepared by Dampney Company, Inc.

85 Paris Street Everett, MA 02149

Tel. 617-389-2805 Fax. 617-389-0484 Email mail@dampney.com

Preparation Date (mm/dd/yyyy): 08/18/2021

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805



DISCLAIMER

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or the user to ensure that this material is properly and safely used.

Last Page